

owandy

REAL HI-T
intra/extra oral camera

A true to-life image




Straightforward,
light and multifunctional,
the new Real Hi-T camera

gives you true-to-life images.

Its durable composite hand-piece
is easy to grasp and maneuver,
plus it has all the most up-to-date
technological innovations.

800.293.7939

Prices subject to change without notice. All logos are rights of respective companies.



REAL HI-T INTRA/EXTRAORAL CAMERA

A True-to-Life Image

The image, digitized at the source via a High Tech CDD sensor, reproduces every detail in natural color.

The Proof is on the Screen

With images to show your patients, you can explain and support your diagnosis from the screen.

A Camera with Varied Talents

Real Hi-T instantly shows the captured images and with a single click, allows you to freeze and archive the images you consider essential.

One Camera, Two Configurations

Video or digital, the Real Hi-T camera connects via USB port to any PC in your practice, allowing for ingenious resource sharing. Its can also be used in independent mode.

A Library of Patients' Images

Selected, framed and retouched, each image is archived in the patient file, to be easily consulted for future treatment.



...or reality itself

Straightforward, light and multifunctional, the new Real Hi-T camera gives you true-to-life images. Its durable composite hand-piece is easy to grasp and maneuver, plus it has all the most up-to-date technological innovations, making the Real Hi-T a top-of-the-line camera.

Technical Specifications

Hand-Piece

Digital sensor 1/4" Sony CDD, 752 X 576 pixels (PAL)
768 X 494 pixels (NTSC)

Video standard PAL or NTSC

Lighting Five White LEDs

Length 212 mm

Thickness 22 X 11.5 mm

Weight 80 g

Sharpness 2 mm to infinity

Focus Multifunction button and micro-motor

Image freeze Foot pedal

Hand-piece button

Modes One or four images

Intra and extra-oral

Cable Dual connection

Ø 5 mm, length ≤ 10 m

Video Version

Size 160 x 103 x 37 mm

Interface Y/C Video and composite video output

Compact Flash reader

Foot pedal

Memory Compact Flash card

Power supply 12 V table/24 V AC chair

USB Version

Size Connection box 120 x 60 x 30

Interfaces PC USB 2.0 connection

Freeze pedal

Standards CE/IPX7 compliant